

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
22 March 2001 (22.03.2001)

PCT

(10) International Publication Number
WO 01/19267 A1

(51) International Patent Classification⁷: **A61B 17/80**

(21) International Application Number: PCT/CH00/00474

(22) International Filing Date:
6 September 2000 (06.09.2000)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/153,239 13 September 1999 (13.09.1999) US

(71) Applicant (for all designated States except CA, US): SYN-
THES AG CHUR [CH/CH]; Grabenstrasse 15, CH-7002
Chur (CH).

[US/US]; 345 Blacksmith Road, Douglassville, PA 19518
(US). MAST, Jeff, W. [US/US]; 64 Pointe Park Place,
Grosse Pointe Park, MI 48230 (US). MAYO, Keith, A.
[US/US]; 29820 Riverside Bay Court, Harrison Township,
MI 48045 (US). BOLHOFNER, Brett, R. [US/US]; 1771
Tanglewood Drive NE, St. Peterbourg, FL 33702 (US).
LITTLE, David [US/US]; P-273, 300 East Evans Street,
West Chester, PA 19380 (US).

(74) Agent: LUSUARDI, Werther; Dr. Lusuardi AG,
Kreuzbühlstrasse 8, CH-8008 Zürich (CH).

(81) Designated States (national): AU, CA, CN, JP, KR, US,
ZA.

(84) Designated States (regional): European patent (AT, BE,
CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC,
NL, PT, SE).

(71) Applicant (for CA only): SYNTHES (U.S.A.) [US/US];
1690 Russell Road, P.O. Box 1766, Paoli, PA 19301-1222
(US).


Published:
— With international search report.

(72) Inventors; and

(75) Inventors/Applicants (for US only): WEAVER, Paul, C.

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: BONE PLATE SYSTEM



(57) Abstract: The present invention relates to a bone plating system and method for fracture fixation of bone. The bone plating system includes a bone plate (30; 50; 80), at least one locking screw (20), and at least one non-locking screw (10). The bone plate (30; 50; 80) has locking holes (36; 56; 86) with threads (40) and non-locking holes (38; 58; 88). The locking screws (20) have a shaft (26) with a thread for engaging bone and a head (22) with a thread (24) configured and dimensioned to mate with the thread (40) of the locking holes (36; 56; 86). The non-locking screws (10) have a thread for engaging bone and a non-threaded head (12). Both the locking and non-locking screws (20; 10) remain seated in their respective holes (36; 56; 86; 38; 58; 88) for substantially as long as the bone plate (30; 50; 80) is implanted. The non-locking screws (10) compress the bone plate (30; 50; 80) against the bone and hold fracture reduction while the locking screws (20) are secured to the plate at a fixed angular relationship. The mixed fixation achieved by this bone plating system and method is particularly useful for treatment of per-articular fractures.

WO 01/19267 A1

BONE PLATE SYSTEM

The present invention is directed to a bone plating system for fracture fixation, and in particular to a system including a bone plate having plate holes for both locking and non-locking screws.

The clinical success of plate and screw systems for internal fixation of fractures is well-documented. However, treatment of certain fractures, such as peri-articular fractures, which require a fixed angular relationship between the bone plate and screws, remains problematic. Fixed angle devices for treatment of these fractures are available and include the Dynamic Condylar Screw System commercially available from Synthes (USA) of Paoli, PA and a wide variety of blade plates. All of these devices require a high level of surgical skill, suitable bone quantity and quality, and a fracture pattern compatible with the device.

In cases in which these requirements are not satisfied, e.g. severely comminuted bone or missing bone segments, conventional bone plate and screw systems must be used. Although these conventional systems are particularly well-suited to promoting healing of the fracture by compressing the fracture ends together and drawing the bone into close apposition with other fragments and the bone plate, the angular relationships between the plate and screws are not fixed and can change postoperatively. This can lead to mal-alignment and poor clinical results.

The primary mechanism for the change in angular relationship is related to energy storage. As previously noted, threading a bone screw into bone compresses the bone against the plate. The compression results in high strain in the bone, and, consequently, energy storage. With the dynamic loading resulting from physiological conditions, loosening of the plate and screw and loss of the stored energy can result.

Securing the screws to the plate provides a fixed angle relationship between the plate and screw and reduces the incidence of loosening. One method of securing the screw to the plate involves the use of so-called "locking screws". A locking screw has threading on an outer surface of its head that mates with corresponding threading on the surface of a plate hole to lock the screw to the plate. Bone plates

having threaded holes for accommodating locking screws are known. For example, German Patent Application No. 43 43 117 discloses a bone plate with threaded holes for locking screws. As the relationship between the locking screws and the plate is fixed, locking screws provide a high resistance to shear or torsional forces. However, locking screws have a limited capability to compress bone fragments.

In summary, conventional bone screws, i.e. screws that are not secured to a plate so that a fixed angular relationship between the plate and screw is maintained (hereinafter "non-locking screws") effectively compress bone fragments, but possess a low resistance to shear force that can lead to loosening of the screw. Locking screws have a high resistance to shear force that ensure stability at the bone screw/plate hole interface, but possess a limited ability to compress bone fragments. Thus, a bone plating system that combines non-locking screws with locking screws would be ideal for certain clinical situations.

U.S. Patent No. 5,601,553 discloses a locking plate and bone screw. The plate has a plurality of threaded plate holes for receiving locking screws. The plate also has non-threaded plate holes for receiving temporary screws that keep the plate in place while the locking screws are inserted. After the locking screws are inserted, the temporary screws are removed. Thus, the long term benefits of combining non-locking screws with locking screws are not obtained. U.S. Patent No. 5,709,686 discloses a bone plate with partially threaded plate holes. The partially threaded holes allow either non-locking or locking screws to be used. Because the plate holes are only partially threaded, the locking screws used may not be able to maintain the fixed angular relationship between the screws and plate under physiological loads. Specifically, the locking screws within the plate are only partially captivated and thus only partially surrounded by threads. Under high stress and loading conditions, the locking plate hole may distort and allow the fixed angular relationship between the locking screw and plate to change. This can result in loss of fixation or loss of established intraoperative plate orientation. Additionally, because of the plate hole geometry, translation of the plate with the non-locking screws is limited to one direction only. This may be a disadvantage in reduction and manipulation of fragments.

Thus, there exists a need for an improved bone plating system that overcomes the deficiencies of the prior art.

The bone plating system for fixation of bone according to the present invention includes a bone plate having an upper surface, a bone-contacting surface, at least one first hole passing through the upper and bone-contacting surfaces and having a thread, and at least one second hole passing through the upper and bone-contacting surfaces. The bone plating system also includes a first screw having a shaft with a thread for engaging bone and a head with a thread configured and dimensioned to mate with the thread of the first hole, and a second screw having a shaft with a thread for engaging bone and a head. The first and second screws remain seated in their respective holes for substantially as long as the bone plate is implanted. Preferably, the bone plate includes a plurality of first and second holes, and a corresponding plurality of first and second screws are provided.

In order to facilitate insertion, the first and second screws can be a self-tapping screws. These screws can also be self-drilling screws. Additionally, the first and second screws can be cannulated for insertion of a guide wire to guide screw placement. The first plate hole can have a substantially conical shape with a double-lead thread.

In one embodiment, the bone plate has a trapezoidal shaped cross section in regions between the first and second plate holes for minimizing contact between bone and the bone-contacting surface. Additionally, at least one of the second plate holes is longitudinally elongated and has an edge inclined at an angle to the upper surface toward the bone-contacting surface for displacing the bone plate when engaged by the head of a second bone screw.

In an exemplary embodiment, the bone plate includes a head portion configured and dimensioned to conform to a metaphysis of a bone and a shaft portion configured and dimensioned to conform to a diaphysis of a bone. The head portion has only first plate holes and the shaft portion has both first and second plate holes. In one embodiment, the head portion has a curved surface, includes an anterior fork substantially parallel to an anterior side of the shaft portion, and includes a posterior

fork extending out from a posterior side of the shaft portion. In another embodiment, the head portion flares outward from the shaft portion and is curved, tapered, and twisted. The head portion can also be provided with suture holes from suture anchoring of the bone plate.

The method for fracture fixation of bone according to the present invention comprises the steps of reducing the fracture to bring bone fragments in close apposition; compressing a bone plate against the bone with at least one first fastener to hold the fracture reduction; and securing at least one second fastener at a fixed angular relationship to the bone plate. The first fasteners are inserted before the second fasteners and both the first and second fasteners remain in bone for substantially as long as the bone plate is implanted.

Brief Description of the Drawings

FIG. 1 is a side view of one embodiment of a non-locking screw according to the present invention;

FIG. 2 is a side view of one embodiment of a locking screw according to the present invention;

FIG. 3 is a perspective view of a portion of a bone plate according to the present invention;

FIG. 4 shows a cross-sectional view of one of the first plate holes through line 4-4 of FIG. 3;

FIG. 5 shows a cross-sectional view of one of the second plate holes through line 5-5 of FIG. 3;

FIG. 6 shows another cross-sectional view of the second plate hole of FIG. 5 through line 6-6 of FIG. 3;

FIG. 7 shows a top view of an embodiment of a bone plate according to the present

invention designed for use in the distal femur;

FIG. 8 shows a side view of the bone plate of FIG. 7;

FIG. 9 shows a perspective view of the bone plate of FIG. 7 implanted in a distal femur;

FIG. 10 shows a top view of the bone plate of FIG. 7 with various cross sections labeled;

FIG. 11 shows a cross-section of the bone plate of FIG. 7 through line A-A;

FIG. 12 shows a cross-section of the bone plate of FIG. 7 through line B-B;

FIG. 13 shows a cross-section of the bone plate of FIG. 7 through line C-C;

FIG. 14 shows a cross-section of the bone plate of FIG. 7 through line D-D;

FIG. 15 shows a cross-section of the bone plate of FIG. 7 through line E-E;

FIG. 16 shows a cross-section of the bone plate of FIG. 7 through line F-F;

FIG. 17 shows a cross-section of the bone plate of FIG. 7 through line G-G;

FIG. 18 shows a cross-section of the bone plate of FIG. 7 through line H-H;

FIG. 19 shows a cross-section of the bone plate of FIG. 7 through line I-I;

FIG. 20 shows a side view of an embodiment of a bone plate according to the present invention designed for use in the proximal tibia;

FIG. 21 shows a top view of the bone plate of FIG. 20;

FIG. 22 shows a perspective view of the bone plate of FIG. 20 implanted in a

proximal tibia;

FIG. 23 shows an end view of the bone plate of FIG. 20 with various cross sections labeled;

FIG. 24 shows a cross-section of the bone plate of FIG. 21 through line A-A;

FIG. 25 shows a cross-section of the bone plate of FIG. 21 through line I-I; and

FIG. 26 shows a cross-section of the bone plate of FIG. 21 through line D-D.

Description of the Preferred Embodiments

The bone plating system according to the present invention includes a bone plate, non-locking screws, and locking screws. FIG. 1 shows an example of a non-locking screw 10 that can be used with the present invention. In general and as described in more detail below, any surgical screw that has a non-threaded head 12 of an appropriate size and geometry for select plate holes of the bone plate can be used. Non-locking screw 10 has a shaft 14 that is at least partially threaded for attachment to bone. The length of shaft 14 and the shaft thread configuration can be selected for the particular application. As is well known in the art, the threads and a tip 16 can be made to be self-tapping and/or self-drilling to facilitate implantation. Shaft 14 can also be cannulated with a channel for receiving a guide wire to aid in proper placement.

FIG. 2 shows an example of a locking screw 20 that can be used with the present invention. In general and as described in more detail below, any surgical screw that has a head 22 with threads 24 can be used as long as head 22 is of an appropriate size and geometry for select plate holes of the bone plate and threads 24 mate with the threads of the plate holes. Locking screw 20 has a shaft 26 that is at least partially threaded for attachment to bone. The length of shaft 26 and the shaft thread configuration can be selected for the particular application. As is well known in the art, the threads and a tip 28 can be made to be self-tapping and/or self-drilling to facilitate implantation. Shaft 26 can be cannulated for receiving a guide wire.

FIG. 3 shows a portion of a bone plate 30 according to the present invention. Bone plate 30 can be made in different shapes and sizes for use in a wide variety of clinical applications. Bone plate 30 includes an upper surface 32 and a bone contacting surface 34. Bone plate 30 has a plurality of first plate holes 36 and a plurality of second plate holes 38. Each of first and second plate holes 36, 38 passes through upper 32 and bone-contacting surfaces 34. Each first plate hole 36 has a thread 40 that mates with thread 24 on head 22 of locking screw 20 to secure locking screw 20 to bone plate 30 at a temporally fixed angular orientation. Second plate holes 38 are not threaded and receive non-locking screws 10 with non-threaded heads 12. Insertion of non-locking screws 10 in second plate holes 38 draws the bone toward bone-contacting surface 34 to compress the bone. Thus, seating of non-locking screws 10 in second plate holes 38 compresses the bone against bone-contacting surface 34 and seating of locking screws 20 in first plate holes 36 secures heads 22 to bone plate 30 for maintaining a fixed angular relationship between locking screws 20 and bone plate 30. Simultaneous use of bone plate 30 with both non-locking and locking screws 10, 20 for as long as bone plate 30 is implanted provides stability between both the screw and bone plate and between the bone plate and bone. As non-locking screws 10 are generally secured in cancellous bone, the threads on shaft 14 are typically larger than the threads on shaft 26 of locking screws 20.

First plate holes 36 are preferably conical in shape. As shown in FIG. 4, threads 40 on first plate holes 36 are also preferably double lead threads. The double lead conical threads enables multiple threads to engage while maintaining a low profile. Additionally, the double lead conical threads are less susceptible to cross-threading compared to other threads, e.g. cylindrical threaded arrangements.

As seen best in FIGS. 5 and 6, second plate holes 38 are preferably dynamic compression unit (DCU) screw holes substantially similar to those disclosed in reissued U.S. Patent No. Re. 31,628 to Allgower et al. , the contents of which are incorporated herein by reference. The DCU screw holes promote healing of the bone by compressing the fracture ends together. Briefly, second plate holes 38 have an edge 42 which includes an oblique portion or ramp 44 having an inclination such that when ramp 44 is engaged by the underside of head 12 of non-locking screw 10, bone

plate 30 is displaced in a direction to move ramp 44 away from non-locking screw 10 and to cause bone plate 30 to apply a pressure to hold the fracture ends in tight engagement.

Bone-contacting surface 34 on bone plate 30 can be shaped to minimize contact with bone. Limiting contact between the bone plate and bone has a number of biological and mechanical advantages including reduced damage to blood supply and easier plate removal. Providing bone plate 30 with a trapezoidal cross section (FIG. 11) in the regions between first and second plate holes 34, 36 is one way to minimize contact. Other ways are disclosed in U.S. Patent Nos. 5,151,103; 5,053,036; 5,002,544; and 4,838,252. The contents of these patents are incorporated herein by reference.

By combining locking screws and non-locking screws on the same bone plate, the present invention provides a novel mixed fixation. With the non-locking screws, fracture reduction is held by friction between the bone plate and bone. This friction is generated by tightening the non-locking screws in bone. However, micromotion between the non-locking screws and bone leads to bone resorption, and loss of reduction. Additionally, insertion of the non-locking screws requires bone to withstand the stresses of tightening of the screws. This results in high stress in bone surrounding the non-locking screws. Ordinarily, the high stress can cause the non-locking screw threads to strip (threads in bone fail in shear) and/or creep in bone (since bone is a viscoelastic material). Either one of these phenomenon also results in loss of reduction.

By adding at least one locking screw, loss of reduction is minimized or eliminated by the present invention. Specifically, by securing the locking screws to the bone plate and not the bone, the effect of the viscoelastic behavior of bone is reduced, the threads do not strip, and micromotion is prevented. The attachment between the locking screws and bone plate is a high strength connection in which the locking screw must cut sideways through bone to fail.

As management of certain peri-articular fractures typically involves insertion of screws at various angles with respect to the bone plate and it is highly desirable to

maintain the initial angular relationships between the individual screws and the bone plate, the bone plating system according to the present invention is particularly well-suited for these clinical applications. FIGS. 7-19 show a bone plate 50 according to the present invention specifically designed for use in the distal femur. Bone plate 50 would be used primarily for, but not limited to, severely comminuted fractures including Hoffa type fractures.

Bone plate 50 has an upper surface 52 and a bone-contacting surface 54. Bone plate 50 has a plurality of threaded plate holes 56a, 56b, 56c (collectively referred to as threaded plate holes 56) for receiving locking screws 20 and a plurality of non-threaded plate holes 58 for receiving non-locking screws 10. Each of threaded and non-threaded plate holes 56, 58 passes through upper 52 and bone-contacting surfaces 54. As was the case for bone plate 30, the thread on threaded plate holes 56 mates with threaded head 22 of locking screw 20 to secure locking screw 20 to bone plate 50 at a temporally fixed angular orientation and insertion of non-locking screws 10 in non-threaded plate holes 58 draws the bone toward bone-contacting surface 54 to compress the bone.

Bone plate 50 includes a head portion 60 configured and dimensioned to conform to the metaphysis of the distal femur and a shaft portion 62 configured and dimensioned to conform to a diaphysis of a bone. As best seen in FIG. 8, bone contacting surface 54 of head portion 60 is a curved surface to fit the contours of the distal femur. Head portion 60 includes an anterior fork 64 substantially parallel to an anterior side 66 of shaft portion 62 and a posterior fork 68 extending laterally out from a posterior side 70 of shaft portion 62.

The non-threaded plate holes 58 are preferably dynamic compression unit (DCU) screw holes substantially similar to second plate holes 38. Shaft portion 62 has both threaded plate holes 56a and non-threaded plate holes 58 so that both locking and non-locking screws can be used in shaft portion 62. The ability to use locking screws in shaft portion 62 is particularly useful when the far cortex of part of the diaphysis is missing or severely damaged since fixation with non-locking screws is problematic because of the condition of the far cortex. As best seen in FIG. 11, the regions between threaded and non-threaded plate holes 56a, 58 have a trapezoidal cross

section that limits contact between bone-contacting surface 54 of shaft portion 62 and the femur. Shaft portion 62 terminates in a tapered tail 72 (FIG. 19).

In contrast to shaft portion 62, head portion 60 contains only threaded holes 56. Specifically, threaded plate holes 56b that surround a centrally located threaded plate hole 56c. Threaded plate hole 56c has a larger diameter than threaded plate holes 56b to accommodate a locking screw with a larger diameter, e.g. threaded plate hole 56b have a diameter of 5.0 mm and threaded plate hole 56c has a diameter of 7.3 mm. FIGS. 12-18 show the various angular orientations of the individual threaded holes 56b, 56c. In generally, threaded holes 56b, 56c are arranged so that the inserted locking screws converge towards each other. It should be noted that, if a surgeon elects, non-locking screws can be used in any of threaded plate holes 56. Finally, it should also be noted that bone plate 50 has several structural differences from the condylar buttress plate commercially available from Synthes (U.S.A.) of Paoli, Pennsylvania. For example, the head of the condylar buttress plate is contoured in both the longitudinal and transverse directions while head portion 60 of bone plate 50 is contoured only in the longitudinal direction for a more anatomical fit. Additionally, tail 72 has an elevated end to get under tissue.

FIGS. 20-26 show a bone plate 80 according to the present invention specifically designed for use in the proximal tibia. Bone plate 80 would be primarily used for, but not limited to fractures of the lateral proximal tibial plateau. Bone plate 80 has an upper surface 82 and a bone-contacting surface 84. Bone plate 80 has a plurality of threaded plate holes 86a, 86b and 86c (collectively referred to as threaded plate holes 86) for receiving locking screws 20 and a plurality of non-threaded plate holes 88 for receiving non-locking screws 10. Each of threaded and non-threaded plate holes 86 and 88 pass through upper 82 and bone-contacting surfaces 84. As was the case for bone plate 30, the threads on threaded plate holes 86 mate with the threaded head 22 of locking screw 20 to secure locking screw 20 to bone plate 80 at a fixed angular orientation. Insertion of non-locking screws 10 in non-threaded plate holes 88 draws the bone-contacting surface 84 toward the bone to compress the plate to the bone.

Bone plate 80 includes a head portion 90 configured and dimensioned to conform to

the metaphysis of the lateral proximal tibia and a shaft portion 92 configured and dimensioned to conform to a diaphysis of the lateral proximal tibia. As seen in FIGS. 20 and 26, bone contacting surface 84 of head portion 90 is a curved, tapered, and twisted to fit the contours of the lateral proximal tibial plateau. Head portion 90 also features sutures holes for suture anchoring and for provisional fixation of bone plate 80.

The non-threaded plate holes 88 are preferably dynamic compression unit (DCU) screw holes substantially similar to second plate holes 38. Shaft portion 92 has both threaded plate holes 86a and non-threaded plate holes 88 so that both locking and non-locking screws can be used in shaft portion 92. The ability to use locking screws in shaft portion 92 is particularly useful when the far cortex of part of the diaphysis is missing or severely damaged since fixation with non-locking screws is problematic because of the condition of the far cortex. As best seen in FIG. 24, the regions between threaded and non-threaded plate holes 86a and 88 have a rectangular cross section that limits contact between bone-contacting surface 84 of shaft portion 92 and the tibia. Shaft portion 92 terminates in a tapered tail 102 (FIG. 25).

In similar fashion to shaft portion 92, head portion 90 contains threaded holes 86 and non-threaded holes 88. Head portion 90 features threaded plate holes 86b and 86c. Holes 86b and 86c have a diameter of 5.0 mm and are oriented as shown in FIGS. 23 and 26. In general, threaded holes 86b, 86c are arranged so that the inserted locking screws converge towards each other. As shown in FIG. 23, plate holes 86b are oriented to converge at a predetermined distance from plate surface 84 to optimize the position of locking screws 20 within the tibia plateau. As shown in FIG. 26, plate hole 86c is oriented to converge with plate hole 86b at predetermined distance to provide additional stability to the locked fixed-angle construct. It should be noted that if a surgeon elects, non-locking screws can be used in any of threaded plate holes 86.

While it is apparent that the illustrative embodiments of the invention herein disclosed fulfil the objectives stated above, it will be appreciated that numerous modifications and other embodiments may be devised by those skilled in the art. For example, for some fractures only one first plate hole and one second plate hole are needed,

although at least two of each is advantageous. Furthermore, additional plate holes without screws can be present in the plate, if desired to allow the surgeon further flexibility in use. Therefore, it will be understood that the appended claims are intended to cover all such modifications and embodiments which come within the scope of the present invention.

Claims

1. A bone plating system for fixation of bone comprising:

a bone plate (30;50;80) having:

an upper surface (32;52;82);

a bone-contacting surface (34;54;84);

at least one first hole (36;56;86) passing through the upper and bone-contacting surfaces (32;52;82;34;54;84) and having a thread (40); and

at least one second hole (38;58;88) passing through the upper and bone-contacting surfaces (32;52;82;34;54;84);

a first screw having a shaft (26) with a thread for engaging bone and a head (22) with a thread (24) configured and dimensioned to mate with the thread of the first hole (36;56;86); and

a second screw having a shaft (14) with a thread for engaging bone and a head (12),

wherein the first and second screws remain seated in their respective holes (36;56;86;38;58;88) for substantially as long as the bone plate (30;50;80) is implanted.

2. The bone plating system of claim 1 wherein the bone plate (30;50;80) includes a plurality of first and second holes (36;56;86;38;58;88), and a corresponding plurality of first and second screws are provided.

3. The bone plating system of claim 1 wherein the first screw is a self-tapping screw.

4. The bone plating system of claim 3 wherein the first screw is a self-drilling screw.

5. The bone plating system of claim 1 wherein the first screw is cannulated for insertion of a guide wire to guide screw placement.
6. The bone plating system of claim 1 wherein the second screw is a self-tapping screw.
7. The bone plating system of claim 1 wherein the first plate hole (36;56;86) has a substantially conical shape.
8. The bone plating system of claim 7 wherein the first plate hole (36;56;86) has a double-lead thread (40).
9. The bone plating system of claim 1 wherein the bone plate (30;50;80) has a trapezoidal shaped cross section in regions between the first and second plate holes (36;56;86;38;58;88) for minimizing contact between bone and the bone-contacting surface (34;54;84).
10. The bone plating system of claim 2 wherein at least one of the second plate holes (38;58;88) is longitudinally elongated and has an edge (41) inclined at an angle to the upper surface (32;52;82) toward the bone-contacting surface (34;54;86) for displacing the bone plate (30;50;80) when engaged by the head of a second bone screw.
11. The bone plating system of claim 2 wherein the bone plate (30;50;80) includes a head portion (60;90) configured and dimensioned to conform to a metaphysis of a bone and a shaft portion (62;92) configured and dimensioned to conform to a diaphysis of a bone.
12. The bone plating system of claim 11 wherein the head portion (60;90) has only first plate holes (36;56;86).
13. The bone plating system of claim 11 wherein the shaft portion (62;92) has both first and second plate holes (36;56;86;38;58;88).

14. The bone plating system of claim 11 wherein the head portion (60;90) has a curved surface, includes an anterior fork substantially parallel to an anterior side of the shaft portion (62;92), and includes a posterior fork extending out from a posterior side of the shaft portion (62;92).

15. The bone plating system of claim 11 wherein the shaft has a trapezoidal shaped cross section in regions between the first and second screw holes (36;56;86;35;58;88) for minimizing contact between bone and the bone-contacting surface (34;54;84).

16. The bone plating system of claim 11 wherein the head portion (60;90) flares outward from the shaft.

17. The bone plating system of claim 15 wherein the head portion (60;90) is provided with suture holes.

18. A method for fracture fixation of bone comprising the steps of:

reducing the fracture to bring bone fragments in close apposition;



compressing a bone plate (30;50;80) against the bone with at least one first fastener to hold the

fracture reduction; and



securing at least one second fastener at a fixed angular relationship to the bone plate (30;50;80),

wherein the at least one first fastener is inserted before the at least one second fastener and the at least one first fastener and the at least one second fastener remain in bone for substantially as long as the bone plate (30;50;80) is implanted.




1/9

*Fig. 1**Fig. 2*

2/9

*Fig. 3**Fig. 9*

3/9

*Fig. 4**Fig. 5**Fig. 6*




Fig. 7




Fig. 8

5/9




Fig. 10




Fig. 11




Fig. 12




Fig. 13




Fig. 14




Fig. 15







Fig. 16

7/9

*Fig. 17**Fig. 18**Fig. 19*

8/9




Fig. 20




Fig. 21




Fig. 22

9/9




Fig. 23



Fig. 24




Fig. 25




Fig. 26

INTERNATIONAL SEARCH REPORT

International Application No

PCT/CH 00/00474

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 A61B17/80

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A61B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EP0-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 709 686 A (TALOS GILBERT ET AL) 20 January 1998 (1998-01-20) cited in the application	1,2
A	column 2, line 26 - line 67; figures 1,2,5-7	10
X	EP 0 486 762 A (LIN KWAN CHUN) 27 May 1992 (1992-05-27)	1,2
A	column 2, line 30 - line 55; figure 1	10
A	US 5 129 901 A (DECOSTE VERN X) 14 July 1992 (1992-07-14)	3-6
A	column 3, line 46 - line 61; figure 3	
A	US 4 838 252 A (KLAUE KAJ) 13 June 1989 (1989-06-13) cited in the application abstract	9

☐ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

° Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

14 December 2000

Date of mailing of the international search report

20.12.00

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, T.x. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Georgiou, Z

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/CH 00/00474

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5709686 A	20-01-1998	WO 9629948 A	03-10-1996
		AU 692846 B	18-06-1998
		AU 1944895 A	16-10-1996
		DE 59508718 D	19-10-2000
		EP 0760632 A	12-03-1997
		JP 10501444 T	10-02-1998

EP 0486762 A	27-05-1992	US 5085660 A	04-02-1992
		DE 69109817 D	22-06-1995
		DE 69109817 T	21-09-1995
		ES 2075274 T	01-10-1995

US 5129901 A	14-07-1992	NONE	

US 4838252 A	13-06-1989	CH 668174 A	15-12-1988
		AT 47514 T	15-11-1989
		BR 8604062 A	17-11-1987
		CA 1320083 A	13-07-1993
		DE 3666528 D	30-11-1989
		EP 0217085 A	08-04-1987
		HK 99392 A	18-12-1992
		JP 1693304 C	17-09-1992
		JP 3054580 B	20-08-1991
		JP 62053646 A	09-03-1987

INTERNATIONAL SEARCH REPORT

International application No.
PCT/CH 00/00474

Box I Observations where certain claims were found unsearchable (Continuation of item 1 of first sheet)

This International Search Report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☒ Claims Nos.: 18
because they relate to subject matter not required to be searched by this Authority, namely:
Rule 39.1(iv) PCT - Method for treatment of the human or animal body by therapy or surgery
2. ☐ Claims Nos.:
because they relate to parts of the International Application that do not comply with the prescribed requirements to such an extent that no meaningful International Search can be carried out, specifically:
3. ☐ Claims Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box II Observations where unity of invention is lacking (Continuation of item 2 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

1. ☐ As all required additional search fees were timely paid by the applicant, this International Search Report covers all searchable claims.
2. ☐ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this International Search Report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this International Search Report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest.
- ☐ No protest accompanied the payment of additional search fees.